

Appln No. 10/760259  
Amtd. Dated: November 17, 2006  
Response to Office Action of October 26, 2006

4

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

### Listing of Claims:

1. – 12. (Cancelled).

13. (Currently Amended) An inkjet printer cradle comprising:  
a body defining an elongate recess dimensioned to locate a removable inkjet cartridge, ~~the body~~  
having an elongate opening sized to allow the inkjet cartridge to be placed in the elongate recess, the  
inkjet cartridge having a pagewidth printhead, an ink storage volume and a fluid connection between  
the printhead and the ink storage volume, the elongate recess having a shelf facing the elongate  
opening, the shelf being inclined with respect to the direction of movement of the inkjet cartridge  
during insertion into the elongate recess, such that sliding engagement with the shelf guides the inkjet  
cartridge during insertion;  
a retainer arranged to retain the inkjet cartridge within the elongate recess; and  
a plurality of resilient members for biasing the inkjet cartridge against the retainer; wherein,  
at least one of the resilient members is positioned proximate one end of the elongate recess and at least  
one other of the resilient members is positioned proximate the other end of the elongate recess.
14. (Currently Amended) An inkjet printer cradle according to claim 13 wherein ~~the body has an elongate~~  
~~opening sized to allow the inkjet cartridge to be placed in the elongate recess,~~ the shelf provides  
mounting points for the resilient members, the inkjet cartridge having a complementary face for  
engaging the resilient members; wherein,  
if the inkjet cartridge is held slightly skew to the elongate recess as it is placed in the cradle, the  
~~complementary~~complementary face will bear against one of the resilient members proximate one of the  
ends of the shelf until the inkjet cartridge is fully inserted into the elongate recess.
15. (Currently Amended) An inkjet printer cradle according to claim 14 wherein the retainer is a latch  
hinged to one side of the elongate opening for rotating into engagement with a catch on the other side  
of the elongate opening in order to form a barrier across the elongate opening.
16. (Previously Presented) An inkjet printer cradle according to claim 15 wherein the plurality of resilient  
members are two coil springs located in circular recesses in the shelf in the elongate recess, one spring  
proximate each end of the elongate recess, and both springs being equidistant from the latch.